



THE LX ELITE ELEVEN

Consider 11 Reasons why the LX Series is the Smart Solution!



1 FUNCTIONAL FLUSH PLUG

- Easy lift, flexible material allows you to quickly pop off flush plug without having to unscrew
- Lift the turret for nozzling so you can save time (and your pinky!)

2 SURE GRIP CAP

- Wet or muddy-hand friendly
- Available non-potable cover fits snugly on cap for identifying reclaimed water

3 SUPERIOR SEAL

- 10-year rating; exceeds 11,000 cycles in sand burial tests
- One piece seal design prevents cap to body leaks
- Ultra-low flushing design enables pop-up & sealing at only 5 psi and allows more heads to be installed on a line
- Extra long wiper seal design provides extended life and positive retraction in the toughest conditions

4 RUGGED RATCHET

- Beefy two-piece ratchet teeth provide just the right feel; not too light where the head could inadvertently move the arc, not too tight where you can't adjust under pressure
- Try one and compare!

5 READY CHECK™ CHECK VALVE

- Prevent low head drainage by purchasing the affordable LX-CV models
- With the ability to hold back 9.5' of elevated water, the LX-CV brings the industry an economical way to conserve water lost to low head drainage
- Combine the LX-CV with the standard Ready Check™ check valve on the Weathermatic Turbo rotor line for a totally checked water conserving system

6 SUPERIOR MATERIAL

- Weathermatic uses only 100% virgin material – no regrind
- For added strength: eight internal reinforcements and a ribbed body

7 LX MPR NOZZLES



- Excellent edge-to-edge watering and performance
- Consistent patterns across each nozzle in the bag
- Color-coded identification in a resealable bag

8 LX ADJUSTABLE ARC NOZZLES



- The ultimate nozzle for flexibility in the field and reducing nozzle inventories
- Arcs are easily adjusted by hand using sure-grip ridges or by coin/screwdriver in slot
- Color-coded identification in a resealable bag

9 LX B SERIES BRASS NOZZLES

- The best performing spray nozzle in the business, period.
- Wide nozzle spacing selection 3', 10', 12', 15', 18', 20' and 24', plus strip nozzles
- Extended spacing gets the job done with fewer heads and less cost by saving pipe, wire, fittings, and labor



10 5 YEAR WARRANTY

- With millions of LX heads and nozzles installed worldwide, return rates are less than a fraction of 1%, even with a 5-year trade warranty

11 LX VALUE

- Considering all of these benefits, you will be amazed to buy the LX line of sprays and nozzles at an extremely competitive price
- Try the entire LX Series and experience the LX difference!

LX

Professional Spray Sprinklers for commercial and residential turf and groundcover applications

LX MODEL SPECIFICATION

STANDARD		
Model	Pop-up Height	METRIC
LX3	3"	7,6 cm
LX4	4"	10 cm
LX6	6"	15 cm
LX12	12"	30 cm
LX4-CV	4"	10 cm
LX6-CV	6"	15 cm
LX12-CV	12"	30 cm
LX-NP	Snap-on cover	
LX-EXT	6" riser extension	

DIMENSIONS

1/2" FEMALE THREADED INLETS

STANDARD		
Model	Body Height	METRIC
LX3	5 1/4"	13,3 cm
LX4	6 1/4"	15,9 cm
LX6	8 1/2"	21,6 cm
LX12	15 1/4"	38,7 cm
Exposed Cover	2 1/4"	5,7 cm

PRE-INSTALLED MODELS

FEATURING LX ADJUSTABLE ARC NOZZLES

Model	Description
LX4-8A	LX4 with 8' Adjustable Arc nozzle
LX4-10A	LX4 with 10' Adjustable Arc nozzle
LX4-12A	LX4 with 12' Adjustable Arc nozzle
LX4-15A	LX4 with 15' Adjustable Arc nozzle
LX4-17A	LX4 with 17' Adjustable Arc nozzle

LXS SHRUB ADAPTER



- 1/2" female inlet threads
- Durable plastic construction
- Threaded to accept MPR, Adjustable Arc, B Series, and all industry-standard female nozzles
- Accepts all LX nozzle protective screens (shipped with nozzle)



FACTORY INSTALLED
LX CHECK VALVE



LX-NP
NON-POTABLE COVER



LX-EXT
6" RISER EXTENSION



LX3



LX4



LX6



LX12

LX SERIES

OPERATING DATA

- Pressure range: 15 – 70 psi (1,0 – 4,8 bars)
- Flow-by: Zero @ 5 psi (0,3 bars) or greater
- Factory installed check valve: 9.5 ft/hd @ 18 psi (2.9 m/hd @ 1,2 bar). Specify: LX4-CV, LX6-CV or LX12-CV
- Compatible with all industry-standard female thread nozzles
- Ratchet nozzle alignment
- Side and bottom inlets on LX6 and LX12*

* Side inlet installation on LX6 and LX12 is not recommended in freezing climates.

DOWNLOAD TECH SPECS AT:
www.weathermatic.com